

NEWTECH

PRECISION • POWER • PERFORMANCE

MODEL
777


SOLDERING & DESOLDERING STATION

All-in-One Solution for Professional Results



DUAL FUNCTION

Soldering and desoldering in one compact station.




PRECISE DIGITAL CONTROL

Independent temperature display and control for soldering and desoldering.



POWERFUL VACUUM

Strong suction for efficient and clean desoldering.



ADJUSTABLE SETTINGS

Vacuum and pressure adjustment for optimal performance.




RELIABLE & DURABLE


Built with high-quality components for long-lasting use.




IDEAL FOR




Electronics Repair



PCB Assembly



Manufacturing



Education & Training

TECHNICAL SPECIFICATIONS

Soldering Temperature Range	200°C – 480°C
Desoldering Temperature Range	200°C – 480°C
Temperature Display	Digital LED
Vacuum	≥ 0.08 MPa
Pressure	0 – 0.8 MPa
Power Supply	AC 220V / 50Hz
Power Consumption	600W
Dimensions (L x W x H)	250 x 185 x 150 mm
Weight	5.0 kg (Approx.)

KEY HIGHLIGHTS

- ✓ Simultaneous soldering & desoldering
- ✓ Stable performance & quick heating
- ✓ Ergonomic handles for comfortable use
- ✓ ESD-safe design for sensitive components
- ✓ Suitable for lead-free soldering

